


NOTES: UNLESS OTHERWISE SPECIFIED  
 1. CONFIGURATIONS WILL BE VALIDATED BY SALES REPRESENTATIVE.

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
A	-	INITIAL RELEASE	J.C.	06/23/2011	-
B	1800 1835 2365	DRAWING FORMAT & NOTES UPDATE	K.T.	03/31/2016	-



TYPE	
M	OM1 Multimode 62um
N	OM2 Multimode 50um
J	OM3 Multimode 50um
H	OM4 Multimode 50um
S	OS2 Singlemode
T	OS2 Bend Insensitive Singlemode

POLISH	
P	PC
S	SPC
A	APC
U	UPC
B	APC/UPC

FIBER COUNT	
01	Simplex
02	Duplex
04	4 Fibers
↓	
96	96 Fibers
44	144 Fibers
88	288 Fibers

JACKET	
L	LSZH 2mm
K	LSZH 3mm
U	OFNP 1.6mm
W	OFNP 1.8mm
Q	OFNP 2mm
P	OFNP 3mm

B	900um
T	OFNR 1.6mm
V	OFNR 1.8mm
S	OFNR 2mm
R	OFNR 3mm

D	Outdoor
F	Fan Out
G	MIC 250um
I	Indoor
T	Flat Drop Tenable
V	Aerial

CABLE TYPE	
A	Armored
B	OSP Armored
C	I/O Armored
H	MIC 250um Armored

J	3mm Round
R	Ribbon
S	Simplex
W	DFX®
Z	ZIP

CONNECTOR 1 / CONNECTOR 2	
LB	LC-NoClip
LC	LC-Clip
LD	LC-Clip 45deg Boot
LG	LC-Clip 90deg Boot
LE	LC-Clip Short Boot
LH	LC-NoClip Short Boot
LS	LC Uniboot

SB	SC-NoClip
SC	SC-Clip
SD	SC-NoClip Short Boot
SE	SC-Clip Short Boot
SG	SC-Clip 90deg Boot
ST	ST
SU	ST Short Boot

ML	MTP Elite
MN	MTP Elite Pins
MP	MTP Pins
MT	MTP
MR	MTP 24F Pins
MS	MTP 24F

FC	FC
MJ	MTRJ
MX	MTRJ-Pins
XX	Unterminated

PRODUCT FAMILY	
P	Performa
R	Performa Connectors/Corning Glass-Print Cable
S	Supra
T	Corning Connectors/Corning Glass-Print Cable
U	Ultra

EXTRAS	
P	Pulling Eye, Staggering Connectors
Q	2 Pulling Eye, Staggered
R	Pulling Eye, Config Straight Through
C	Config Straight Through
S	Staggered Connectors
T	Staggered, Config Straight Through

BREAKOUT	
E	C-BREAK Single 3mm
F	C-BREAK Single 2mm
I	C-BREAK Single 900um
C	C-BREAK Y 3mm
G	C-BREAK Y 2mm
M	C-BREAK Y 3/2mm

9	900um
Q	Reverse C-Term, 3mm
R	Reverse C-Term, 2mm
T	C-Term
S	Straight Through A-A / B-B
X	Cross Over A-B / B-A

MTP to MTP	
S	Type A
X	Type B
P	Type C

UNITS	
M	Meters
F	Feet
I	Inches
LENGTH	
As requested	
CUSTOMER / OTHER	
5	36in Breakout
8	48in Breakout
9	12in Breakout
J	18in Breakout
B	Tracer Identifier Boot
I	Individual Bag

LABELS / REPORTS	
K	1 Label
L	2 Labels
R	Test Report
S	Test Report, 2 Labels
T	Test Report, 1 Label
F	Interferometer Test
E	Corning Low Loss Spec. Test Report

DRAWN BY:	K. THOMAS	02/17/2016
APVD BY:	A. JENSEN	03/31/2016

C ENTERPRISES  
 2445 CADES WAY  
 VISTA CA 92081  
 760-599-5111

Product Range	
Product	Description
Performa	Performance cable and connectors
Supra	Corning cable and performance connectors
Ultra	Corning cable and connectors

DIMENSIONS: METRIC [IMPERIAL]  
 PROPRIETARY AND CONFIDENTIAL  
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF C ENTERPRISES. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.

TITLE: FIBER PART NUMBER		
SIZE	DWG. NO.	REV
A	FIBER-PART-NUMBER-ALT	B
SCALE: NOT TO SCALE		SHEET 1 OF 1