

Ratcheting Crimper Frame

- Professional CATV, electrical, home theater, satellite and security system ratcheting crimper frame with optional dies is perfect for fast, reliable connector installations
- Full-cycle ratchet action assures a complete, precise crimp every cycle
- Preset tension for optimum performance
- Ratchet mechanism is designed to prevent the release of the connector prior to full compression
- Safety crimp release helps eliminate rejected terminations due to incorrect positioning
- Steel body with black-oxide finish for corrosion resistance and durability
- Thumb-screws secure die-sets for quick, easy changes
- Optional, quick interchangeable die sets thumb and Phillips screw set available (see table)



VDV200-010

| Cat. No. | Handle Color | Overall Length |
|------------|--------------|------------------|
| VDV200-010 | Black/Yellow | 8.75" (222.3 mm) |

NOTE: Use caution when tightening thumb screws to prevent thread damage/stripping and hand tighten only; do not over-tighten the thumb screws. Over-tightening thumb-screws can damage the tool and/or die set.

Coaxial Hex-Crimp Die Sets

| Cat. No. | Die Set | Nest Dimension | Cat. No. | Die Set | Nest Dimension | Cat. No. | Die Set | Nest Dimension |
|------------|--|---|------------|---|---|------------|--|---|
| VDV999-033 | Replacement Screw Set (Thumb and Phillips) | N/A | VDV211-037 | RG58/RG59/ RG6/RG62 | 0.256"/ 0.319"/ 0.068"/ 0.213"/ 6.50/ 8.10/ 1.73/5.41 mm | VDV211-041 | RG58/RG59/ RG6/RG62 | 0.255"/0.213"/ 0.098"/0.068"/ 0.321" 6.48/ 5.41/2.49/ 1.73/8.15 mm |
| VDV212-034 | CATV F Connectors RG59 RG6 | 0.255"/ 0.320"/ 0.350" 6.48/ 8.13/ 8.89 mm | VDV211-038 | RG58/RG59/ RG6/RG62 | 0.256"/0.068"/ 0.213"/6.50/ 1.73/5.41 mm | VDV201-042 | RG174/RG179/ Belden 8218 and Fiber Optic | 0.042"/0.068"/ 0.078"/ 0.128"/ 0.151"/0.178"/ 1.07/7.73/1.98/ 3.25/3.84/ 4.52 mm |
| VDV205-035 | Insulated Terminals, AWG 10-22 | AWG 22-18/ 16-14/12-10 DIN 0.5-1.0/ 1.5-2.5/ 4-6 mm | VDV205-039 | Pin Terminal Insulated or Non-Insulated Ferrules, AWG 12-22 | AWG 22/20/18/ 16/14/12 DIN 0.5/0.75/ 1.0/ 1.5/2.5/ 4 mm | VDV211-043 | RG8/RG11/ RG174/RG179/ RG213 | 0.100"/0.128"/ 0.429" 2.54/ 3.25/10.90 mm |
| VDV205-036 | Non-Insulated Terminal or Open Barrel Terminal, AWG 10-20 | AWG 20-18/ 16, 14/12-10 DIN 0.5-1.5- 2.5/4 - 6 mm | VDV201-040 | RG58/RG59/ RG62/RG174 Fiber Optic | 0.043"/ 0.068"/ 0.100"/ 0.137"/ 0.213"/ 0.255"/ 1.09/1.73/2.54/ 3.48/5.41/6.48 mm | VDV205-044 | Non-Insulated Terminal, AWG 8-18 | AWG 18-16/14 /12-10/8 DIN 0.75-1.5/ 2.54/ 4-6/ 10 mm |

Can Wrench

- Two tools in one; saves space in your pouch
- One end opens telephone box fasteners, the other end tightens nuts on binding-post terminals
- The 7/16" socket has a black finish and the 3/8" socket has a silver finish
- Sockets are 1.25" (32 mm) deep to fit over long binding posts and are thin-walled for easy access into tight areas
- Hex-socket design enables using a wrench to obtain extra torque
- High-impact, break-resistant handle for long and dependable service
- Sockets are heat-treated, alloy steel



68005

| Cat. No. | Socket Size | Handle Diameter | Overall Length |
|----------|------------------------|-----------------|----------------|
| 68005 | 3/8" and 7/16" Hex Nut | 1" (25.4 mm) | 7" (177.8 mm) |