

FPX-2FRP08-962



FPX Fiber Termination/Splice Panel, 96 LC/UPC, pre-terminated with pigtailed, singlemode, 2RU, 19 in, putty white

Product Classification

Product Series	FPX
Product Type	Fiber patch/splice panel
Regional Availability	Latin America North America

Construction Materials

Fiber Mode	Singlemode
Fiber Type	OS1
Finish	Powder coated
Material Type	Aluminum

Dimensions

Depth	304.80 mm 12.00 in
Height	88.90 mm 3.50 in
Width	482.60 mm 19.00 in

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-40 °C to +85 °C (-40 °F to +185 °F)

General Specifications

Rack Units	2.0
Shelf Movement	Fixed
Adapter Packs Included, quantity	4
Body Style	Symmetrical
Color	Putty white
Color, front	Putty white
Functionality	Patching Splicing
Growth Configuration	Fully loaded
Includes	Mounting hardware
Interface Feature, front	Standard
Interface, front	LC
Package Quantity	1

FPX-2FRP08-962

Patching Capacity, maximum	96
Rack Type	EIA 19 in EIA 23 in
Splicing Type	Heat shrink, single fiber fusion
Total Ports, quantity	96

Mechanical Specifications

Cable Exit Location	Rear, left side Rear, right side
----------------------------	------------------------------------

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant

