



Flush floor raceway with removable cover plates. Cover plate is 1/4in (6.4mm) thick and three pieces are supplied for 5ft (1.5m) and 6ft (1.8m) lengths (5ft cover is two 24in and one 12in sections and 6ft cover is three 24in sections). Partitions and supports not included. Length, width, and depth described in catalog number represent outside cover plate and body dimensions. The interior size of the trenchduct bodies is always 13/16in (21mm) narrower than the cover plate. The interior depth of the trenchduct bodies is always 5/16in (7.9mm) shallower than depth specified by catalog number. Body is 16 gauge steel. Vinyl trim and leveling feet are included. Can be leveled to screed depth using leveling foot or support coupling up to 3/4in (19.1mm). Use catalog numbering system to select product. Consult Wiremold sales representative for custom sizes.

Features & Benefits

This product meets the material restrictions of RoHS

Specifications

General Info

Product Line	Wiremold	UPC Number	786564108467
Country Of Origin	United States	Application Sector	Commercial
Standard	cULus Listed Cellular Metal Floor Raceway Fittings: File E26663 Guide RINV/RINV7	Type	Trenchduct

Dimensions

Product Width US	12.0 in	Product Depth US	2.5 in
Product Length US	60.0 in		

Listing Agencies / 3rd Party Agencies

cULus ListingNumber	E26663	cULus Listed	Yes
---------------------	--------	--------------	-----

Additional Information

RoHS Conformant	Yes
-----------------	-----