

# 760118349 | M2400A-1U-GS

---

GigaSPEED X10D® Xpress® U/UTP Angled Single-Row Modular Panel, 24 port (MGS400/500/600)

## Product Classification

|                              |   |
|------------------------------|---|
| <b>Regional Availability</b> | Asia   Australia/New Zealand   EMEA   Latin America   North America |
| <b>Portfolio</b>             | CommScope®  |
| <b>Product Type</b>          | RJ45 patch panel  |
| <b>Product Brand</b>         | GigaSPEED X10D®   |

## General Specifications

|                              |            |
|------------------------------|------------|
| <b>ANSI/TIA Category</b>     | 6   6A     |
| <b>Cable Type</b>            | Unshielded |
| <b>Color</b>                 | Black      |
| <b>Intelligence Type</b>     | Passive    |
| <b>Panel Style</b>           | Angled     |
| <b>Rack Type</b>             | EIA 19 in  |
| <b>Rack Units</b>            | 1          |
| <b>Total Ports, quantity</b> | 24         |

## Dimensions

|   |                     |
|---|---------------------|
| <b>Height</b>                                       | 43.69 mm   1.72 in  |
| <b>Width</b>  | 482.6 mm   19 in    |
| <b>Depth</b>  | 138.18 mm   5.44 in |
| <b>Compatible Diameter Over Dielectric, maximum</b> | 1.168 mm   0.046 in |
| <b>Compatible Diameter Over Dielectric, minimum</b> | 0.762 mm   0.03 in  |

## Material Specifications

|                      |   |
|----------------------|---|
| <b>Material Type</b> | High-impact, flame retardant, thermoplastic   Powder-coated steel |
|----------------------|---|

## Environmental Specifications

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Operating Temperature</b> | -10 °C to +60 °C (+14 °F to +140 °F) |
| <b>Storage Temperature</b>   | -40 °C to +70 °C (-40 °F to +158 °F) |
| <b>Relative Humidity</b>     | Up to 95%, non-condensing            |
| <b>Flammability Rating</b>   | UL 94 V-0                            |
| <b>Safety Standard</b>       | UL   cUL                             |

## Packaging and Weights

|                           |   |
|---------------------------|---|
| <b>Packaging quantity</b> | 1 |
|---------------------------|---|

## Regulatory Compliance/Certifications

| <b>Agency</b> | <b>Classification</b>  |
|---------------|--|
| CHINA-ROHS    | Below maximum concentration value  |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system   |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant  |

