

Flood-Seal® multi-port connectors

Aluminum Flood-Seal multi-port connectors – RAB series



RAB 1/0-21



RAB 1/0-3



RAB 6-C

High-performance, dual-rated connectors.

- Flood-Seal insulating rockets serve as waterproof spare outlet caps until used and are also resealable
- 6061-T6 aluminum connector construction provides high strength and high conductivity
- Dual-rated to accept a wide range of aluminum and copper conductors
- All connectors are 100% hi-pot tested at 4000 V for 60 seconds
- RAB 1/0 series offers compact design – great for street light applications
- RUS Accepted

RAB 1/0 series

Cat. no.	Conductor range (AWG or kcmil)	Outlets	Length (in.)
RAB 1/0-2	#14–1/0	2	1 ³ / ₄
RAB 1/0-3		3	2 ³⁹ / ₆₄
RAB 1/0-4		4	3 ⁷ / ₁₆
RAB 1/0-5		5	4 ⁹ / ₃₂
RAB 1/0-6		6	5 ¹ / ₈
RAB 1/0-7		7	5 ³¹ / ₃₂
RAB 1/0-8		8	6 ¹³ / ₁₆
RAB 1/0-9		9	7 ²¹ / ₃₂
RAB 1/0-10		10	8 ¹ / ₂
RAB 1/0-21		3	2 ³⁹ / ₆₄
RAB 1/0-22		4	3 ⁷ / ₁₆
RAB 1/0-31		4	3 ⁷ / ₁₆
RAB 1/0-32		5	4 ⁹ / ₃₂
RAB 1/0-33		6	5 ¹ / ₈
RAB 1/0-42		6	5 ¹ / ₈

Note: For oxide-inhibitor option, add “-C” suffix to the catalog number.

RAB 350 series

Cat. no.	Conductor range (AWG or kcmil)	Outlets	Length (in.)
RAB 2-C	#12 sol.–350	2	2 ⁷ / ₁₆
RAB 3-C		3	3 ⁵ / ₈
RAB 4-C		4	4 ¹³ / ₁₆
RAB 5-C		5	6
RAB 6-C		6	7 ¹ / ₈
RAB 8-C		8	9 ⁹ / ₁₆
RAB 10-C		10	11 ¹⁵ / ₁₆

Note: The RAB 350 series comes standard with inward-seal rockets. For outward-seal rockets, please consult your ABB representative. Provided with oxide inhibitor.

01 For EZ Torque® shear-head screws supplied in all outlets, add “-TS” suffix to the catalog number.



01