

### Main

Range	Multi9
Product name	Multi9 GFP
Product or Component Type	Residual current circuit breaker (RCCB)
Device short name	GFP
Device Application	Distribution
Poles description	4P
Neutral position	Left
Line Rated Current	25 A 104 °F (40 °C) EN/IEC 61008-1
Network type	AC
Earth-leakage sensitivity	86 MA UL 1053 100 mA EN/IEC 61008-1
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A-SI (Super Immunised)
Utilisation category	AC-23A EN/IEC 61008-1
Standards	EN/IEC 61008-1 UL 1053
Product certifications	IEC[RETURN]UL

### Complementary

Network Frequency	50/60 Hz
[Ue] rated operational voltage	415 V AC 50 Hz 480Y/277 V AC 60 Hz
Residual current tripping technology	Voltage independent
Rated breaking and making capacity	Idm 1500 A EN/IEC 61008-1
Rated conditional short-circuit current	Inc 10 kA 100 A gG
[Ui] rated insulation voltage	440 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kVEN/IEC 61008-1
Contact position indicator	Yes
Control Type	Toggle
Local signalling	ON, OFF, fault trip
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 mm pitches	8
Height	3.2 in (81 mm)
Width	2.8 in (72 mm)
Depth	2.4 in (60 mm)
Net Weight	0.99 lb(US) (0.45 kg)
Color	Gray
Mechanical durability	20000 cycles
Locking options description	Padlocking in OFF position
Connections - terminals	Tunnel type terminals top or bottom) 0.002...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) AWG 18...AWG 3) - flexible Tunnel type terminals top or bottom) 0.002...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) AWG 18...AWG 2) - rigid Tunnel type terminals top or bottom) 0.002...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) AWG 18...AWG 3) - flexible with ferrule
Wire stripping length	0.6 in (14 mm) for top or bottom connection
Tightening torque	31.0 lbf.in (3.5 N.m) top or bottom

## Environment

IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3
Electromagnetic compatibility	8/20 $\mu$ s impulse withstand, 3000 A EN/IEC 61008-1
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)

## Ordering and shipping details

Category	US10DE200948
Discount Schedule	0DE2
GTIN	3606481198518
Returnability	Yes
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.62 in (9.2 cm)
Package 1 Width	3.03 in (7.7 cm)
Package 1 Length	3.35 in (8.5 cm)
Package 1 Weight	12.3 oz (350.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	27
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	21.907 lb(US) (9.937 kg)

## Offer Sustainability

Packaging without single use plastic	Yes
Packaging made with recycled cardboard	Yes
SCIP Number	2c7837a4-39fc-4abc-96ed-2ef14f8f87c7
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	No