

# FTL-C/C-P001M

---



TracerLight® Fiber Optic Patch Cord, 1.7 mm simplex, singlemode, LC/UPC to LC/UPC, RBR, blue, 1 m

- Offers a quick and accurate method of identifying the termination point of optical patch cords
- Each end of a TracerLight patch cord features a flashing light source allowing technicians to visually trace individual patch cords
- Dramatically minimizes the risk of taking the wrong fiber out of service while improves system turn-up speed and accuracy
- Ideally suited for Central Offices, Data Centers and cross-connect patching

## Product Classification

<b>Regional Availability</b>	Latin America   North America
<b>Product Type</b>	Fiber patch cord, simplex
<b>Product Brand</b>	TracerLight®
<b>Product Series</b>	FTL

## General Specifications

<b>Color, boot A</b>	Blue
<b>Color, boot B</b>	Blue
<b>Color, connector A</b>	Blue
<b>Color, connector B</b>	Blue
<b>Connector A, quantity</b>	1
<b>Connector B, quantity</b>	1
<b>Interface, Connector A</b>	LC/UPC
<b>Interface, Connector B</b>	LC/UPC
<b>Jacket Color</b>	Blue
<b>Total Fibers, quantity</b>	1

## Dimensions

<b>Cord Length</b>	1 m   3.281 ft
<b>Diameter Over Jacket</b>	1.7 mm   0.067 in

## Optical Specifications

<b>Fiber Mode</b>	Singlemode
<b>Fiber Type</b>	G.657.A2

# FTL-C/C-P001M

---

<b>Insertion Loss, maximum, connector A</b>	0.3 dB
<b>Insertion Loss, maximum, connector B</b>	0.3 dB
<b>Return Loss, minimum, connector A</b>	55 dB
<b>Return Loss, minimum, connector B</b>	55 dB

## Environmental Specifications

<b>Environmental Space</b>	Plenum
----------------------------	--------

## Packaging and Weights

<b>Packaging quantity</b>	1
---------------------------	---

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant/Exempted

