

Product data sheet

Characteristics

UGHTRS213C

Individual meter socket, ringless socket, horn bypass, 5 jaws no release, OH, UG, 200 A, up to 600 VAC single phase 3W

Main

Product or Component Type	Meter Socket
Meter socket type	Ringless
Hub type	A ACP closing plate

Complementary

Meter socket rated current	200 A
Number of jaws	5 without jaw release
Bypass type	Horn bypass
Phase	1 phase
[Ue] rated operational voltage	<= 600 V AC
Enclosure Material	Steel
Electrical connection	Lugs 0.5" hex
Service feed location	UG OH
Wiring configuration	3-wire
Device mounting	Surface
AWG gauge	AWG 8...350 kcmil aluminium/copper)line side

Environment

Product Certifications	ANSI[RETURN]UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	US10DE400039
Discount Schedule	0DE4
GTIN	785901282679
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.50 in (13.97 cm)
Package 1 Width	11.80 in (29.972 cm)
Package 1 Length	15.90 in (40.386 cm)
Package 1 Weight	12.899 lb(US) (5.851 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	72

Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	941.846 lb(US) (427.214 kg)

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
California proposition 65	"WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov "
EU RoHS Directive	Under investigation
Take-back	No

Contractual warranty

Warranty	18 months
----------	-----------