

Straight Blade Devices

15A, 125V, 2 Pole, 3 Wire Grounding

Commercial Specification Grade Duplex  
Receptacles for Controlled Applications



Features

- Permanently marked with universal power symbol and the word "CONTROLLED" to visually identify receptacles used in automatic energy management systems
- Patented TR design eliminates plug-in difficulty and TR complaints
- Markings can be read regardless of mounting orientation
- Complies with NEC Section 406.3, ASHRAE 90.1, and California Title 24 requirements
- Complements Hubbells Load Logic control system or other available energy management system

Ordering Information

| Description                      | Device Color | UPC Number   | Catalog Number |
|----------------------------------|--------------|--------------|----------------|
| Smooth face, back and side wired | Gray         | 783585582436 | BR15C1GRYTR    |

Listings

Fed. Spec. W-C-596  
UL Listed to UL498 File No. E2186  
Certified to CSA, C22.2, No. 42  
NEMA® WD-6 Compliant

Online Resources

[eCatalog](#)



Specifications

|                                 |                                    |
|---------------------------------|------------------------------------|
| Power Contacts                  | .030 in. (.8) Brass                |
| Ground Contacts                 | Brass                              |
| Face                            | Nylon                              |
| Mounting Screws                 | Galvanized Steel                   |
| Automatic Self-grounding Staple | Stainless steel                    |
| Mounting Strap                  | .040 in. Galvanized steel          |
| Base                            | Nylon                              |
| Wire Clamp                      | .062 in. (1.6) Nickel plated steel |

Performance

|                         |                                                          |
|-------------------------|----------------------------------------------------------|
| <b>Electrical</b>       |                                                          |
| Current Interrupting    | Certified for current interrupting at full rated current |
| Dielectric Voltage      | Withstands 2,000V minimum                                |
| <b>Mechanical</b>       |                                                          |
| Product Identification  | Ratings are a permanent part of the device               |
| Terminal Accommodation  | #14-10 AWG stranded or solid copper wire only.           |
| Terminal Identification | Terminals identified in accordance with UL 498 and CSA   |
| <b>Environmental</b>    |                                                          |
| Flammability            | UL 94V-2                                                 |
| Operating Temperature   | Maximum continuous 75°C; minimum -40°C (w/o impact)      |

