



GE
Lighting

SAFETY & PERFORMANCE

- ANSI_C62
- ANSI_C82
- FCC_Part_18
- No_PCB
- UL_Listed
- UL_Cls_P
- UL_Type1_Out
- cUL_Listed

63097 - High frequency electronic ballasts for 2 or 1 CFL lamps

GEC226-MVPS-3W

- Line Voltage: Multi-Voltage 120 to 277 VAC, +/-10%, 50-60Hz
- Series Lamp Operation
- IC Control
- Programmed starting for extended lamp life
- Active Power Factor Correction

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
FT24W/2G1 1	1	120	27	0.23	1.04		0.99	1.7	10	-20
FT24W/2G1 1	1	277	27	0.11	1.1		0.91	1.7	14	-20
CFQ26W	1	120	30	0.25	1.04		0.99	1.7	10	-20
CFQ26W	1	277	30	0.12	1.04		0.93	1.7	13	-20
FT36W/2G1 1	1	120	35	0.29	0.94		0.99	1.7	10	-20
FT36W/2G1 1	1	277	35	0.13	0.94		0.94	1.7	13	-20
CFTR26W	1	120	32	0.26	1.01		0.99	1.7	10	-20
CFTR26W	1	277	32	0.12	1.0		0.94	1.7	13	-20
CFTR26W	2	120	64	0.53	0.97		0.99	1.7	10	-20
CFTR26W	2	277	64	0.23	0.88		0.97	1.7	12	-20
CFS21W	2	277	55	0.2	1.11		0.96	1.7	11	-20
CFS21W	2	120	56	0.47	1.12		0.99	1.7	10	-20
CFQ26W	2	120	56	0.47	1.02		0.99	1.7	10	-20
CFQ26W	2	277	54	0.2	1.02		0.97	1.7	11	-20
CFTR42W	1	120	51	0.42	0.92		0.99	1.7	10	-20
CFTR42W	1	277	50	0.18	0.92		0.97	1.7	12	-20
FC16T9	1	120	40	0.34	0.89		0.99	1.7	10	-20
FC16T9	1	277	40	0.14	0.94		0.95	1.7	13	-20
CFTR32W/G X24q	1	120	39	0.33	1.24		0.99	1.7	10	
CFTR32W/G X24q	1	277	39	0.15	1.23		0.95	1.7	13	-20
FT39W/2G1 1	1	120	33	0.27	0.97		0.99	1.7	10	-20
FT39W/2G1 1	1	277	33	0.12	0.98		0.94	1.7	14	-20