



Representative

Catalog Number: RAB 1/0-2
Product ID: 7TAA260180R0001
UPC Number: 78378674487
EAN Number: 05415022505733
Status: A

Aluminum Flood-Seal, Multi-Port Connector, RAB 1/0 Series, Conductor Range #14 - 1/0. Santoprene Coated. RUS Accepted. Total Outlets 2. Length 1-3/4 inch. Includes Caps and Screws.

- Flood-Seal Insulating Rockets Serve as Waterproof Spare Outlet Caps until Used and are Also Resealable.
- 6061-T6 Aluminum Connector Construction Provides High Strength and High Conductivity.
- Dual-Rated to Accept a Wide Range of Aluminum and Copper Conductors.
- All Connectors are 100 Percent Hi-Pot Tested at 4000V for 60 Seconds.
- RUS Accepted.
- RAB 1/0 Series offers Compact Design - Great for Street Light Applications.

North American Specifications (UNSPSC)

UNSPSC	39121443 Electrical underground bus connector
IGCC	4663 Electrical underground bus connector
Type	Aluminum Flood-Seal Multi-Port Connector RAB 1/0 Series
Special Features	High Performance, Dual Rated Connectors.
Application	Dual-Rated Connector
Standard	RUS Accepted
Size	1-3/4 inch
Connection	Mechanical
Conductor Range	#14 to 1/0 AWG
Material	6061-T6 Aluminum Connector, Santoprene Body
Color	Black
Insulation	Yes
Number Of Poles	2
Environmental Conditions	Waterproof

Packaging

Outer Quantity	25
Outer Dimensions (inches)	13.25x8.25x7.5
Weight Uom	0.15 lbs. Each

Documents / Support Tools

Catalog Page	Available on Website
Instruction Sheet	0051920-TB2
Catalog	Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com